

Median Filter

Sample User's Guide

Intel® SDK for OpenCL * Applications - Samples

Document Number: 325264-005US

Contents

Contents	2
Legal Information	3
About Median Filter	4
Introduction	4
Motivation	4
Algorithm	5
OpenCL* Implementation	5
Understanding OpenCL Performance Characteristics	6
APIs Used	6
Reference (Native) Implementation	6
Controlling the Sample	6
References	7

Legal Information

INFORMATION IN THIS DOCUMENT IS PROVIDED IN CONNECTION WITH INTEL PRODUCTS. NO LICENSE, EXPRESS OR IMPLIED, BY ESTOPPEL OR OTHERWISE, TO ANY INTELLECTUAL PROPERTY RIGHTS IS GRANTED BY THIS DOCUMENT. EXCEPT AS PROVIDED IN INTEL'S TERMS AND CONDITIONS OF SALE FOR SUCH PRODUCTS, INTEL ASSUMES NO LIABILITY WHATSOEVER AND INTEL DISCLAIMS ANY EXPRESS OR IMPLIED WARRANTY, RELATING TO SALE AND/OR USE OF INTEL PRODUCTS INCLUDING LIABILITY OR WARRANTIES RELATING TO FITNESS FOR A PARTICULAR PURPOSE, MERCHANTABILITY, OR INFRINGEMENT OF ANY PATENT, COPYRIGHT OR OTHER INTELLECTUAL PROPERTY RIGHT.

A "Mission Critical Application" is any application in which failure of the Intel Product could result, directly or indirectly, in personal injury or death. SHOULD YOU PURCHASE OR USE INTEL'S PRODUCTS FOR ANY SUCH MISSION CRITICAL APPLICATION, YOU SHALL INDEMNIFY AND HOLD INTEL AND ITS SUBSIDIARIES, SUBCONTRACTORS AND AFFILIATES, AND THE DIRECTORS, OFFICERS, AND EMPLOYEES OF EACH, HARMLESS AGAINST ALL CLAIMS COSTS, DAMAGES, AND EXPENSES AND REASONABLE ATTORNEYS' FEES ARISING OUT OF, DIRECTLY OR INDIRECTLY, ANY CLAIM OF PRODUCT LIABILITY, PERSONAL INJURY, OR DEATH ARISING IN ANY WAY OUT OF SUCH MISSION CRITICAL APPLICATION, WHETHER OR NOT INTEL OR ITS SUBCONTRACTOR WAS NEGLIGENT IN THE DESIGN, MANUFACTURE, OR WARNING OF THE INTEL PRODUCT OR ANY OF ITS PARTS.

Intel may make changes to specifications and product descriptions at any time, without notice. Designers must not rely on the absence or characteristics of any features or instructions marked "reserved" or "undefined". Intel reserves these for future definition and shall have no responsibility whatsoever for conflicts or incompatibilities arising from future changes to them. The information here is subject to change without notice. Do not finalize a design with this information.

The products described in this document may contain design defects or errors known as errata which may cause the product to deviate from published specifications. Current characterized errata are available on request.

Contact your local Intel sales office or your distributor to obtain the latest specifications and before placing your product order.

Copies of documents which have an order number and are referenced in this document, or other Intel literature, may be obtained by calling 1-800-548-4725, or go to:

<http://www.intel.com/design/literature.htm>.

Intel processor numbers are not a measure of performance. Processor numbers differentiate features within each processor family, not across different processor families. Go to:

http://www.intel.com/products/processor_number/.

Software and workloads used in performance tests may have been optimized for performance only on Intel microprocessors. Performance tests, such as SYSmark and MobileMark, are measured using specific computer systems, components, software, operations and functions. Any change to any of those factors may cause the results to vary. You should consult other information and performance tests to assist you in fully evaluating your contemplated purchases, including the performance of that product when combined with other products.

Intel, Intel logo, Intel Core, VTune, Xeon are trademarks of Intel Corporation in the U.S. and other countries.

* Other names and brands may be claimed as the property of others.

OpenCL and the OpenCL logo are trademarks of Apple Inc. used by permission from Khronos.

Microsoft product screen shot(s) reprinted with permission from Microsoft Corporation.

Copyright © 2010-2013 Intel Corporation. All rights reserved.


Optimization Notice

Intel's compilers may or may not optimize to the same degree for non-Intel microprocessors for optimizations that are not unique to Intel microprocessors. These optimizations include SSE2, SSE3, and SSSE3 instruction sets and other optimizations. Intel does not guarantee the availability, functionality, or effectiveness of any optimization on microprocessors not manufactured by Intel. Microprocessor-dependent optimizations in this product are intended for use with Intel microprocessors. Certain optimizations not specific to Intel microarchitecture are reserved for Intel microprocessors. Please refer to the applicable product User and Reference Guides for more information regarding the specific instruction sets covered by this notice.

Notice revision #20110804

About Median Filter

Median Filter sample demonstrates how to use median filter in OpenCL*. This implementation optimizes filtration process using implicit Single Instruction Multiple Data (SIMD) code vectorization performed by build-in OpenCL compiler vectorizer. Data-level parallelism of the underlying algorithm results in additional performance gain. The sample improves the performance of the method and reduces data loads. The following figure illustrates median filtering.



Refer to the article at <http://tracer.lcc.uma.es/problems/mfp/mfp.html> for more information.

Introduction

Median filter is a non-linear filter that removes noise from an image or a signal. One of the advantages of this method is that it can preserve sharp edges while removing noise. To remove noise, the median filter algorithm processes element patterns of the input image or signal. For each pattern of neighboring elements called *window* or *support*, the algorithm finds the median value that is further used as filtering result for the central element of the window.

Motivation

In general, median filter effect requires a significant number of calculations and color buffer accesses. This sample implementation minimizes color buffer accesses, removes synchronization points, and uses data-level parallelism, which results in significant performance gain and better result quality as compared to applications that use the same filtration technique optimized for traditional GPU architectures. For an example, please see the algorithm implemented for traditional GPUs described in the article at

http://developer.download.nvidia.com/compute/cuda/3_0/sdk/website/OpenCL/website/samples.html.

This sample demonstrates a CPU-optimized implementation of 2D image median filtration, showing how to:

- Implement calculation kernels using OpenCL C99
- Parallelize the kernels by running several work-groups in parallel
- Organize host-device data exchange with final image storage on the hard drive

Algorithm

The median filter processes each pixel in the image and compares it to its neighbors to determine whether this pixel can represent the window entries. It replaces the central pixel value with the *median* of the pixel values in the window.

To define the median of a window, sort the entries of the window numerically. For windows with an odd number of entries, the median is the value of the middle entry. For windows with an even number of entries, several options are possible.

The following figure illustrates a sample calculation of the median value for a pixel neighborhood:

123	125	126	130	140
122	124	126	127	135
118	120	150	125	134
119	115	119	123	133
111	116	110	120	130

Neighborhood values:
115, 119, 120, 123, 124,
125, 126, 127, 150

Median value: 124

This example illustrates a 3×3 square window. As the central pixel value of 150 does not represent the surrounding values well, it is replaced with the median value of 124. Please note that larger windows produce greater smoothing.

The advantage of the median filtering is that unrepresentative pixels in a window cannot have significant effect on the median value. Since the median value must be an actual value of one of the window entries, the median filter does not create new unrealistic pixel values when the filter processes an edge region. Thus, median filtering permits to preserve sharp edges. For details, see article at <http://homepages.inf.ed.ac.uk/rbf/HIPR2/median.htm>.

OpenCL* Implementation

This sample applies the following algorithm stages to a 2D image:

- 3x3 pixels patch load
- partial bitonic sorting
- result storage in 4-channel 32-bit integer format.

In this implementation, MedianFilterBitonic OpenCL* kernel of MedianFilter.cl file uses partial bitonic sorting to perform median filtering. Every input array pixel corresponds to a unique global ID that the kernel uses for their identification. The full median filtering sequence consists of OpenCL kernel call performed in ExecuteMedianFilterKernel() function of MedianFilter.cpp file.

This algorithm implementation consists of the [Pixels Load](#) and [Partial Sort](#) parts.

Pixels Load

This sample uses 32-bit red, green, blue, and alpha (RGBA) pixels, with 8-bit unsigned `char` values representing pixel individual color channel. For further processing, 3x3=9 pixels are preloaded into temporary storage.

Partial Sort

This sample uses an algorithm that operates on 3x3 box-shaped support and performs partial sort to find the fifth sorted value out of 3x3 = 9 values. Partial sort performs 19 MIN and 20 MAX operations

to find median value for 3x3 support for each color channel. The algorithm operates with 32-bit unsigned integer values. For details on this algorithm, see article at <http://www.iti.fh-flensburg.de/lang/algorithmen/sortieren/bitonic/bitonicen.htm> and Frederick M. Waltz, Ralf Hack, and Bruce G. Batchelor. "Fast, efficient algorithms for 3x3 ranked filters using finite-state machines".

Understanding OpenCL Performance Characteristics

Benefits of Implicit Compiler Vectorization

The kernel structure enables implicit vectorization performed by the Intel® OpenCL Offline Compiler when work-group size is multiple of four. Consequently, you can achieve ~2x speedup for the current versions of kernel and vectorizer.

Work-group Size Considerations

The sample uses NULL argument for local work group size to allow runtime to choose sub-optimal workgroup size by itself depending on device.

APIs Used

This sample uses the following APIs:

- `clKreateKernel`
- `clCreateContextFromType`
- `clGetContextInfo`
- `clCreateCommandQueue`
- `clCreateProgramWithSource`
- `clBuildProgram`
- `clCreateBuffer`
- `clSetKernelArg`
- `clEnqueueNDRangeKernel`
- `clEnqueueReadBuffer`
- `clReleaseMemObject`
- `clReleaseKernel`
- `clReleaseProgram`
- `clReleaseCommandQueue`
- `clReleaseContext`

Reference (Native) Implementation

Reference implementation is done in `ExecuteMedianFilterReference()` routine of `MedianFilter.cpp` file. This is single-threaded code that performs exactly the same median filtering sequence as OpenCL implementation, but uses conventional C nested loop.

Controlling the Sample

The sample executable is a console application. You can set the input array size and choose device using command-line arguments:

Option	Description
<code>-h, --help</code>	Show this help text and exit.
<code>-p, --platform number-or-string</code>	Select platform, devices of which are used.
<code>-t, --type all cpu gpu acc default <OpenCL constant for device type></code>	Select the device by type on which the OpenCL kernel is executed.

<code>-d, --device number-or-string</code>	Select the device on which all stuff is executed.
<code>--width <integer></code>	Width of processed image.
<code>--height <integer></code>	Height of processed image.
<code>--errors <integer></code>	Number of errors to print.

If you do not specify the array size, the sample uses the default value of $8192 \times 8192 = 67108864$ items.

References

- <http://tracer.lcc.uma.es/problems/mfp/mfp.html>
- http://developer.download.nvidia.com/compute/cuda/3_0/sdk/website/OpenCL/website/samples.html
- <http://homepages.inf.ed.ac.uk/rbf/HIPR2/median.htm>
- <http://www.itl.fh-flensburg.de/lang/algorithmen/sortieren/bitonic/bitonicen.htm>
- Frederick M. Waltz, Ralf Hack, and Bruce G. Batchelor. Fast, efficient algorithms for 3x3 ranked filters using finite-state machines.
- http://www.engin.umd.umich.edu/~jwvm/ece581/18_RankedF.pdf